




## Data Sheet Type 063-T



### Low voltage halogen desk lamp

<b>Material</b>	Aluminium, Steel
<b>Dimensions</b>	520mm x 580mm
<b>Mobility</b>	800mm
<b>Weight</b>	5,3 KG

<b>Light source</b>	12V/50W Max. GY 6.35
<b>Lifetime of illuminant</b>	4000 hrs.
<b>Transformer</b>	Electronic Converter LET-12V/240V R, LET-75 (USA/Canada)
<b>Approvements</b>	VDE, EMV, CE
<b>Power factor</b>	0,95 Electr. Int. resettable short circuit protection

<b>Input</b>	230/240V 50/60Hz , 110/120V 50/60Hz (USA/Canada)
<b>Maximum load</b>	75W
<b>Minimum load with dimmer</b>	20W
<b>Input current at max. load</b>	0,31A
<b>Length of powercord</b>	2,05 m

- Aluminium diecast frame with high polished surface without electroplating sealing.
  - Deepdrawing bipartite aluminium Lighthousing with high gloss two-component wet painting.
  - Chilled cast iron base with shape cutting chipping technology. High gloss two-component wet painting.
  - On/off toggle switch with short stem and ball positioned in the base.
- All joints are connected with polyoxymethylen (POM) plastic parts, low mechanical attrition. All joints are connected with screws and adjustable. No visible wires, midsection and lighthousing are equipped with sliding contacts for maximal mobility.

<b>Packaging</b>	Box, 1250mm x 240mm x 240mm Double facted corrugated board Protection inside with polystyrene form parts
<b>Weight</b>	7 KG